




Carbide long drills with oil holes

# DEEP HOLE DRILLS

Volume 1.1



# INDEX

---


## DEEP HOLE DRILLS

ADO-10D .....	PAGE 4-5
ADO-15D <i>NEW SIZES</i> .....	PAGE 6-7
ADO-20D <i>NEW SIZES</i> .....	PAGE 8-9
ADO-25D .....	PAGE 10
ADO-30D <i>NEW SIZES</i> .....	PAGE 11
ADO-40D <i>NEW SIZES</i> .....	PAGE 12
ADO-50D <i>NEW SIZES</i> .....	PAGE 13
CAO-GDXL .....	PAGE 14
Cutting conditions .....	PAGE 15

## TECHNICAL INFORMATION DEEP HOLE DRILLING

Technical information .....	PAGE 16-19
Cutting Data .....	PAGE 20-21

# ENTER THE WORLD OF ULTRA-EFFICIENT DEEP-HOLE 50XD DRILLING



## R Gash

Unique R gash geometry enables super low cutting resistance and exceptional chip control


## New flute specification

New flute specification with smooth chip evacuation and high tool rigidity qualities ideal for ultra-deep-hole applications

## Highly rigid 25° helical flute

## R Gash Geometry

Breaks chips into small and manageable pieces with superior chip evacuation capability



Work Material: SUS304

## EgiAs Coating

EgiAs coating with high toughness and wear resistance characteristics

Constructed with extreme toughness, high wear and heat resistance characteristics to ensure stable and consistent tool life.



# EgiAs



Coating Color	Coating Structure	Hardness (GPa)	Oxidation Temperature (C°)	Heat Resistance	Adhesion Strength	Surface Roughness	Wear Resistance	Welding Resistance	Toughness
Interference Color	Periodic Nano-layered	40	1.100	☉	☉	○	☉	☉	☉

# ADO-10D

Drilling | Solid carbide | 10xD



- First choice in quality and performance
- Carbide drill with internal coolant, EgiAs coating
- Double margin, up to 10xD
- For general purpose steels and cast iron
- 102 sizes



Drilling | Solid carbide


10xD

EDP	DC	LCF	OAL	DCON	EDP	DC	LCF	OAL	DCON
8696200	2	26	75	3	8710660	6,6	87	140	8
8696210	2,1	33	75	3	8710670	6,7	87	140	8
8696220	2,2	33	75	3	8710680	6,8	90	140	8
8696230	2,3	33	75	3	8710690	6,9	90	140	8
8696240	2,4	33	75	3	8710700	7	90	140	8
8696250	2,5	33	75	3	8710710	7,1	100	155	8
8696260	2,6	40	90	3	8710720	7,2	100	155	8
8696270	2,7	40	90	3	8710730	7,3	100	155	8
8696280	2,8	40	90	3	8710740	7,4	100	155	8
8696290	2,9	40	90	3	8696750	7,5	100	155	8
8696300	3	40	90	3	8710760	7,6	105	155	8
8696310	3,1	45	100	4	8710770	7,7	105	155	8
8696320	3,2	45	100	4	8710780	7,8	105	155	8
8696330	3,3	45	100	4	8710790	7,9	105	155	8
8696340	3,4	50	100	4	8696800	8	105	155	8
8696350	3,5	50	100	4	8710810	8,1	110	165	10
8696360	3,6	50	100	4	8710820	8,2	110	165	10
8696370	3,7	50	100	4	8710830	8,3	110	165	10
8696380	3,8	50	100	4	8710840	8,4	110	165	10
8696390	3,9	50	100	4	8710850	8,5	110	165	10
8696400	4	50	100	4	8710860	8,6	115	165	10
8710410	4,1	55	115	6	8710870	8,7	115	165	10
8710420	4,2	55	115	6	8710880	8,8	115	165	10
8710430	4,3	60	115	6	8710890	8,9	115	165	10
8710440	4,4	60	115	6	8710900	9	115	165	10
8710450	4,5	60	115	6	8710910	9,1	125	190	10
8710460	4,6	60	115	6	8710920	9,2	125	190	10
8710470	4,7	65	115	6	8710930	9,3	125	190	10
8710480	4,8	65	115	6	8710940	9,4	125	190	10
8710490	4,9	65	115	6	8696950	9,5	125	190	10
8710500	5	65	115	6	8710960	9,6	130	190	10
8710510	5,1	70	128	6	8710970	9,7	130	190	10
8710520	5,2	70	128	6	8710980	9,8	130	190	10
8710530	5,3	70	128	6	8710990	9,9	130	190	10
8710540	5,4	78	128	6	8697000	10	130	190	10
8696550	5,5	78	128	6	8711010	10,1	140	205	12
8710560	5,6	78	128	6	8711020	10,2	140	205	12
8710570	5,7	78	128	6	8711030	10,3	140	205	12
8710580	5,8	78	128	6	8711040	10,4	140	205	12
8710590	5,9	78	128	6	8711050	10,5	140	205	12
8696600	6	78	128	6	8711060	10,6	140	205	12
8710610	6,1	87	140	8	8711070	10,7	140	205	12
8710620	6,2	87	140	8	8711080	10,8	145	205	12
8710630	6,3	87	140	8	8711090	10,9	145	205	12
8710640	6,4	87	140	8	8711100	11	145	205	12
8710650	6,5	87	140	8	8711110	11,1	155	215	12



# ADO-15D NEW SIZES

Drilling | Solid carbide | 15xD



- First choice in quality and performance
- Carbide drill with internal coolant, EgiAs coating
- Double margin, up to 15xD
- For general purpose steels and cast iron
- 102 sizes

Solid carbide



Drilling |


15xD

EDP	DC	LCF	OAL	DCON	EDP	DC	LCF	OAL	DCON
48338120	2	36	90	3	8712660	6,6	120	175	8
48338121	2,1	38	90	3	8712670	6,7	120	175	8
48338122	2,2	40	90	3	8712680	6,8	125	175	8
48338123	2,3	42	90	3	8712690	6,9	125	175	8
48338124	2,4	44	90	3	8712700	7	125	175	8
48338125	2,5	45	96	3	8712710	7,1	135	195	8
48338126	2,6	47	96	3	8712720	7,2	135	195	8
48338127	2,7	49	96	3	8712730	7,3	135	195	8
48338128	2,8	51	96	3	8712740	7,4	135	195	8
48338129	2,9	53	96	3	8698750	7,5	135	195	8
8698300	3	55	105	3	8712760	7,6	145	195	8
8698310	3,1	60	125	4	8712770	7,7	145	195	8
8698320	3,2	60	125	4	8712780	7,8	145	195	8
8698330	3,3	60	125	4	8712790	7,9	145	195	8
8698340	3,4	65	125	4	8698800	8	145	195	8
8698350	3,5	65	125	4	8712810	8,1	155	210	10
8698360	3,6	65	125	4	8712820	8,2	155	210	10
8698370	3,7	65	125	4	8712830	8,3	155	210	10
8698380	3,8	75	125	4	8712840	8,4	155	210	10
8698390	3,9	75	125	4	8712850	8,5	155	210	10
8698400	4	75	125	4	8712860	8,6	160	210	10
8712410	4,1	75	140	6	8712870	8,7	160	210	10
8712420	4,2	75	140	6	8712880	8,8	160	210	10
8712430	4,3	85	140	6	8712890	8,9	160	210	10
8712440	4,4	85	140	6	8712900	9	160	210	10
8712450	4,5	85	140	6	8712910	9,1	170	240	10
8712460	4,6	85	140	6	8712920	9,2	170	240	10
8712470	4,7	85	140	6	8712930	9,3	170	240	10
8712480	4,8	90	140	6	8712940	9,4	170	240	10
8712490	4,9	90	140	6	8698950	9,5	170	240	10
8712500	5	90	140	6	8712960	9,6	180	240	10
8712510	5,1	95	160	6	8712970	9,7	180	240	10
8712520	5,2	95	160	6	8712980	9,8	180	240	10
8712530	5,3	95	160	6	8712990	9,9	180	240	10
8712540	5,4	110	160	6	8699000	10	180	240	10
8698550	5,5	110	160	6	8713010	10,1	190	260	12
8712560	5,6	110	160	6	8713020	10,2	190	260	12
8712570	5,7	110	160	6	8713030	10,3	190	260	12
8712580	5,8	110	160	6	8713040	10,4	190	260	12
8712590	5,9	110	160	6	8713050	10,5	190	260	12
8698600	6	110	160	6	8713060	10,6	190	260	12
8712610	6,1	120	175	8	8713070	10,7	200	260	12
8712620	6,2	120	175	8	8713080	10,8	200	260	12
8712630	6,3	120	175	8	8713090	10,9	200	260	12
8712640	6,4	120	175	8	8713100	11	200	260	12
8712650	6,5	120	175	8	8713110	11,1	210	280	12



# ADO-20D NEW SIZES

Drilling | Solid carbide | 20xD



- First choice in quality and performance
- Carbide drill with internal coolant, EgiAs coating
- Double margin, up to 20xD
- For general purpose steels and cast iron
- 102 sizes



EDP	DC	LCF	OAL	DCON	EDP	DC	LCF	OAL	DCON
48338220	2	46	100	3	8714660	6,6	155	210	8
48338221	2,1	49	100	3	8714670	6,7	155	210	8
48338222	2,2	51	100	3	8714680	6,8	160	210	8
48338223	2,3	53	100	3	8714690	6,9	160	210	8
48338224	2,4	56	100	3	8714700	7	160	210	8
48338225	2,5	58	109	3	8714710	7,1	170	230	8
48338226	2,6	60	109	3	8714720	7,2	170	230	8
48338227	2,7	63	109	3	8714730	7,3	170	230	8
48338228	2,8	65	109	3	8714740	7,4	170	230	8
48338229	2,9	67	109	3	8706750	7,5	170	230	8
8706300	3	70	120	3	8714760	7,6	180	230	8
8706310	3,1	80	140	4	8714770	7,7	180	230	8
8706320	3,2	80	140	4	8714780	7,8	180	230	8
8706330	3,3	80	140	4	8714790	7,9	180	230	8
8706340	3,4	85	140	4	8706800	8	180	230	8
8706350	3,5	85	140	4	8714810	8,1	195	260	10
8706360	3,6	85	140	4	8714820	8,2	195	260	10
8706370	3,7	85	140	4	8714830	8,3	195	260	10
8706380	3,8	90	140	4	8714840	8,4	195	260	10
8706390	3,9	90	140	4	8714850	8,5	195	260	10
8706400	4	90	140	4	8714860	8,6	210	260	10
8714410	4,1	100	165	6	8714870	8,7	210	260	10
8714420	4,2	100	165	6	8714880	8,8	210	260	10
8714430	4,3	110	165	6	8714890	8,9	210	260	10
8714440	4,4	110	165	6	8714900	9	210	260	10
8714450	4,5	110	165	6	8714910	9,1	220	290	10
8714460	4,6	110	165	6	8714920	9,2	220	290	10
8714470	4,7	110	165	6	8714930	9,3	220	290	10
8714480	4,8	115	165	6	8714940	9,4	220	290	10
8714490	4,9	115	165	6	8706950	9,5	220	290	10
8714500	5	115	165	6	8714960	9,6	230	290	10
8714510	5,1	120	190	6	8714970	9,7	230	290	10
8714520	5,2	120	190	6	8714980	9,8	230	290	10
8714530	5,3	120	190	6	8714990	9,9	230	290	10
8714540	5,4	140	190	6	8707000	10	230	290	10
8706550	5,5	140	190	6	8715010	10,1	250	310	12
8714560	5,6	140	190	6	8715020	10,2	250	310	12
8714570	5,7	140	190	6	8715030	10,3	250	310	12
8714580	5,8	140	190	6	8715040	10,4	250	310	12
8714590	5,9	140	190	6	8715050	10,5	250	310	12
8706600	6	140	190	6	8715060	10,6	250	310	12
8714610	6,1	155	210	8	8715070	10,7	250	310	12
8714620	6,2	155	210	8	8715080	10,8	250	310	12
8714630	6,3	155	210	8	8715090	10,9	250	310	12
8714640	6,4	155	210	8	8715100	11	250	310	12
8714650	6,5	155	210	8	8715110	11,1	270	330	12

Drilling | Solid carbide



20xD






# ADO-25D

Drilling | Solid carbide | 25xD



- First choice in quality and performance
- Carbide drill with internal coolant, EgiAs coating
- Double margin, up to 25xD
- For general purpose steels and cast iron
- 92 sizes



Ideal for drilling oil channels in crankshafts

<b>P</b>	<b>P</b>	<b>P</b>	<b>P</b>	<b>M</b>	<b>K</b>	<b>K</b>	<b>H</b>
C < 0,2%	0,25 < C < 0,4	C ≥ 0,45%	SCM	INOX	GG	GGG	25-35 HRC

<b>A</b>	<b>CARBIDE</b>	<b>EgiAs</b>	<b>30°</b>	<b>SHRINK FIT</b>		<b>140°</b>	<b>e8</b>
----------	----------------	--------------	------------	-------------------	--	-------------	-----------


EDP	DC	LCF	OAL	DCON	EDP	DC	LCF	OAL	DCON
48338325	2,5	70	121	3	8724750	7,5	210	275	8
8726300	3	85	135	3	8724760	7,6	225	275	8
8724310	3,1	95	165	4	8724770	7,7	225	275	8
8724320	3,2	95	165	4	8724780	7,8	225	275	8
8724330	3,3	95	165	4	8724790	7,9	225	275	8
8724340	3,4	105	165	4	8724800	8	225	275	8
8724350	3,5	105	165	4	8724810	8,1	240	305	10
8724360	3,6	105	165	4	8724820	8,2	240	305	10
8724370	3,7	105	165	4	8724830	8,3	240	305	10
8724380	3,8	115	165	4	8724840	8,4	240	305	10
8724390	3,9	115	165	4	8724850	8,5	240	305	10
8724400	4	115	165	4	8724860	8,6	255	305	10
8724410	4,1	120	190	6	8724870	8,7	255	305	10
8724420	4,2	120	190	6	8724880	8,8	255	305	10
8724430	4,3	135	190	6	8724890	8,9	255	305	10
8724440	4,4	135	190	6	8724900	9	255	305	10
8724450	4,5	135	190	6	8724910	9,1	270	340	10
8724460	4,6	135	190	6	8724920	9,2	270	340	10
8724470	4,7	135	190	6	8724930	9,3	270	340	10
8724480	4,8	140	190	6	8724940	9,4	270	340	10
8724490	4,9	140	190	6	8724950	9,5	270	340	10
8724500	5	140	190	6	8724960	9,6	280	340	10
8724510	5,1	150	220	6	8724970	9,7	280	340	10
8724520	5,2	150	220	6	8724980	9,8	280	340	10
8724530	5,3	150	220	6	8724990	9,9	280	340	10
8724540	5,4	170	220	6	8725000	10	280	340	10
8724550	5,5	170	220	6	8725010	10,1	310	370	12
8724560	5,6	170	220	6	8725020	10,2	310	370	12
8724570	5,7	170	220	6	8725030	10,3	310	370	12
8724580	5,8	170	220	6	8725040	10,4	310	370	12
8724590	5,9	170	220	6	8725050	10,5	310	370	12
8724600	6	170	220	6	8725060	10,6	310	370	12
8724610	6,1	190	250	8	8725070	10,7	310	370	12
8724620	6,2	190	250	8	8725080	10,8	310	370	12
8724630	6,3	190	250	8	8725090	10,9	310	370	12
8724640	6,4	190	250	8	8725100	11	310	370	12
8724650	6,5	190	250	8	8725110	11,1	340	400	12
8724660	6,6	190	250	8	8725120	11,2	340	400	12
8724670	6,7	190	250	8	8725130	11,3	340	400	12
8724680	6,8	200	250	8	8725140	11,4	340	400	12
8724690	6,9	200	250	8	8725150	11,5	340	400	12
8724700	7	200	250	8	8725160	11,6	340	400	12
8724710	7,1	210	275	8	8725170	11,7	340	400	12
8724720	7,2	210	275	8	8725180	11,8	340	400	12
8724730	7,3	210	275	8	8725190	11,9	340	400	12
8724740	7,4	210	275	8	8725200	12	340	400	12

Drilling | Solid carbide

25xD

# ADO-30D NEW SIZES

Drilling | Solid carbide | 30xD



- First choice in quality and performance
- Carbide drill with internal coolant, EgiAs coating
- Double margin, up to 30xD
- For general purpose steels and cast iron
- 81 sizes



EDP	DC	LCF	OAL	DCON	EDP	DC	LCF	OAL	DCON
48338420	2	66	120	3	8716660	6,6	215	280	8
48338421	2,1	70	120	3	8716670	6,7	215	280	8
48338422	2,2	73	120	3	8716680	6,8	230	280	8
48338423	2,3	76	120	3	8716690	6,9	230	280	8
48338424	2,4	80	120	3	8716700	7	230	280	8
48338425	2,5	83	134	3	8716710	7,1	250	315	8
48338426	2,6	86	134	3	8716720	7,2	250	315	8
48338427	2,7	90	134	3	8716730	7,3	250	315	8
48338428	2,8	93	134	3	8716740	7,4	250	315	8
48338429	2,9	96	134	3	8708750	7,5	250	315	8
8708300	3	100	150	3	8716760	7,6	265	315	8
8708310	3,1	102	185	4	8716770	7,7	265	315	8
8708320	3,2	105	185	4	8716780	7,8	265	315	8
8708330	3,3	109	185	4	8716790	7,9	265	315	8
8708340	3,4	112	185	4	8708800	8	265	315	8
8708350	3,5	116	185	4	8716810	8,1	280	350	10
8708360	3,6	116	185	4	8716820	8,2	280	350	10
8708370	3,7	116	185	4	8716830	8,3	280	350	10
8708380	3,8	132	185	4	8716840	8,4	280	350	10
8708390	3,9	132	185	4	8716850	8,5	280	350	10
8708400	4	132	185	4	8716860	8,6	300	350	10
8716410	4,1	140	215	6	8716870	8,7	300	350	10
8716420	4,2	140	215	6	8716880	8,8	300	350	10
8716430	4,3	150	215	6	8716890	8,9	300	350	10
8716440	4,4	150	215	6	8716900	9	300	350	10
8716450	4,5	150	215	6	8716910	9,1	315	390	10
8716460	4,6	150	215	6	8716920	9,2	315	390	10
8716470	4,7	150	215	6	8716930	9,3	315	390	10
8716480	4,8	165	215	6	8716940	9,4	315	390	10
8716490	4,9	165	215	6	8708950	9,5	315	390	10
8716500	5	165	215	6	8716960	9,6	330	390	10
8716510	5,1	180	250	6	8716970	9,7	330	390	10
8716520	5,2	180	250	6	8716980	9,8	330	390	10
8716530	5,3	180	250	6	8716990	9,9	330	390	10
8716540	5,4	200	250	6	8709000	10	330	390	10
8708550	5,5	200	250	6					
8716560	5,6	200	250	6					
8716570	5,7	200	250	6					
8716580	5,8	200	250	6					
8716590	5,9	200	250	6					
8708600	6	200	250	6					
8716610	6,1	215	280	8					
8716620	6,2	215	280	8					
8716630	6,3	215	280	8					
8716640	6,4	215	280	8					
8716650	6,5	215	280	8					









# CUTTING CONDITIONS

Drilling | Solid | Cutting conditions

## ADO-10D/15D/20D/25D/30D

Vc	Mild Steel - Low Carbon Steel SS400 · S10C ~150HB ~500 N/mm <sup>2</sup>		Carbon Steel S35C · S50C ~210HB ~710 N/mm <sup>2</sup>		Alloys Steel SCM · SCr · SNCM 16~28HRC 710~900 N/mm <sup>2</sup>		Cast Iron FC250 ~350 N/mm <sup>2</sup>		Ductile Cast Iron FCD450 · FCD600 400~600 N/mm <sup>2</sup>		Stainless Steel SUS400 400 ~ 800 N/mm <sup>2</sup>	
	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)
60 ~ 125 m/min			60 ~ 125 m/min		60 ~ 125 m/min		60 ~ 125 m/min		50 ~ 80 m/min		40 ~ 80 m/min	
2	11.000	0,04 ~ 0,08	11.000	0,04 ~ 0,08	11.000	0,04 ~ 0,08	11.000	0,04 ~ 0,08	11.000	0,04 ~ 0,08	8.000	0,04 ~ 0,08
3	7.500	0,06 ~ 0,12	7.500	0,06 ~ 0,12	7.500	0,06 ~ 0,12	7.500	0,06 ~ 0,12	7.500	0,06 ~ 0,12	5.300	0,06 ~ 0,12
4	6.400	0,08 ~ 0,16	6.400	0,08 ~ 0,16	6.400	0,08 ~ 0,16	6.400	0,08 ~ 0,16	5.600	0,08 ~ 0,16	5.000	0,08 ~ 0,16
5	5.800	0,10 ~ 0,20	5.800	0,10 ~ 0,20	5.800	0,10 ~ 0,20	5.800	0,10 ~ 0,20	4.500	0,10 ~ 0,20	4.500	0,10 ~ 0,20
6	4.800	0,12 ~ 0,24	4.800	0,12 ~ 0,24	4.800	0,12 ~ 0,24	4.800	0,12 ~ 0,24	3.800	0,12 ~ 0,24	3.800	0,12 ~ 0,24
8	3.600	0,16 ~ 0,28	3.600	0,16 ~ 0,28	3.600	0,16 ~ 0,28	3.600	0,16 ~ 0,28	2.800	0,16 ~ 0,28	2.800	0,16 ~ 0,28
10	2.900	0,20 ~ 0,35	2.900	0,20 ~ 0,35	2.900	0,20 ~ 0,35	2.900	0,20 ~ 0,35	2.300	0,20 ~ 0,35	2.300	0,20 ~ 0,35
12	2.400	0,24 ~ 0,42	2.400	0,24 ~ 0,42	2.400	0,24 ~ 0,42	2.400	0,24 ~ 0,42	1.900	0,24 ~ 0,42	1.900	0,24 ~ 0,42

## ADO-40D/50D

Vc	Mild Steel - Low Carbon Steel SS400 · S10C ~150HB ~500 N/mm <sup>2</sup>		Carbon Steel S35C · S50C ~210HB ~710 N/mm <sup>2</sup>		Alloy Steel SCM · SCr · sncm 16~28HRC 710 ~ 900 N/mm <sup>2</sup>		Alloy Steel (C ≥ 0,3%) SCM440 28~35HRC 900~1,060N/mm <sup>2</sup>	
	S (min <sup>-1</sup> )	f (mm/rev.)	S (min <sup>-1</sup> )	f (mm/rev.)	S (min <sup>-1</sup> )	f (mm/rev.)	S (min <sup>-1</sup> )	f (mm/rev.)
60~90m/min			60~90m/min		50~80m/min		40~70m/min	
3	7.500	0,06 ~ 0,12	7.500	0,06 ~ 0,12	6.400	0,06 ~ 0,12	5.300	0,06 ~ 0,12
4	5.600	0,08 ~ 0,16	5.600	0,08 ~ 0,16	4.800	0,08 ~ 0,16	4.000	0,08 ~ 0,16
5	4.500	0,1 ~ 0,2	4.500	0,1 ~ 0,2	3.800	0,1 ~ 0,2	3.200	0,1 ~ 0,2
6	3.700	0,12 ~ 0,24	3.700	0,12 ~ 0,24	3.200	0,12 ~ 0,24	2.700	0,12 ~ 0,24
8	2.800	0,16 ~ 0,28	2.800	0,16 ~ 0,28	2.400	0,16 ~ 0,28	2.000	0,16 ~ 0,28
10	2.300	0,2 ~ 0,35	2.300	0,2 ~ 0,35	1.900	0,2 ~ 0,35	1.600	0,2 ~ 0,35

Vc	Cast Iron FC250 ~350N/mm <sup>2</sup>		Ductile Cast Iron FCD450 - FCD600 400 ~ 600 N/mm <sup>2</sup>		Stainless Steel SUS300/400 480 ~ 800 N/mm <sup>2</sup>	
	S (min <sup>-1</sup> )	f (mm/rev.)	S (min <sup>-1</sup> )	f (mm/rev.)	S (min <sup>-1</sup> )	f (mm/rev.)
60~90m/min			50~80m/min		40~60m/min	
3	7.500	0,06 ~ 0,12	6.400	0,06 ~ 0,12	5.300	0,06 ~ 0,12
4	5.600	0,08 ~ 0,16	4.800	0,08 ~ 0,16	4.000	0,08 ~ 0,16
5	4.500	0,1 ~ 0,2	3.800	0,1 ~ 0,2	3.200	0,1 ~ 0,2
6	3.700	0,12 ~ 0,24	3.200	0,12 ~ 0,24	2.700	0,12 ~ 0,24
8	2.800	0,16 ~ 0,28	2.400	0,16 ~ 0,28	2.000	0,16 ~ 0,28
10	2.300	0,2 ~ 0,35	1.900	0,2 ~ 0,35	1.600	0,2 ~ 0,35

- The indicated speeds and feeds are for drilling with water-soluble coolant or MQL (mist drilling in stainless steels is not recommended).
- Water-soluble high density coolant (20-30 times dilution) is recommended.
- When using non-water-soluble coolant, set the cutting speed between 70-100% of the lowest limit.
- Make a pilot hole before using in accordance with the recommended operation.
- A clogged oil hole can lead to breakage. Make sure that a filter is attached to the oil feeder.
- Peck drilling of 1D - 2D is strongly recommended.

\*If it is difficult to process or if the straightness of the hole needed to be improved, use the coolant-through carbide drill ADO-20/30D after drilling a pilot hole, then process with the ADO-40/50D. When processing with 3 tools, the ADO-40/50D may be used at a more aggressive cutting condition than those listed above.

## CAO-GDXL

Standard drilling


Vc	AC ADC · AC		Al A20... · A70...		Al A50... · A60...		Cu C1020 · C1100		Cu CrCu	
	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)	S (min <sup>-1</sup> )	F (mm/rev.)
80 ~ 200 m/min			60 ~ 120 m/min		80 ~ 200 m/min		80 ~ 200 m/min		60 ~ 120 m/min	
3	12.800	0,09~0,15	10.700	0,09~0,15	12.800	0,06~0,12	12.800	0,06~0,12	10.700	0,05~0,09
4	9.600	0,12~0,20	8.000	0,12~0,20	9.600	0,08~0,16	9.600	0,08~0,16	8.000	0,06~0,10
5	7.700	0,15~0,25	6.400	0,15~0,25	7.700	0,10~0,20	7.700	0,10~0,20	6.400	0,06~0,10
6	6.400	0,18~0,30	5.400	0,18~0,30	6.400	0,12~0,20	6.400	0,12~0,20	5.400	0,06~0,10
8	4.800	0,20~0,40	4.000	0,20~0,40	4.800	0,12~0,25	4.800	0,12~0,25	4.000	0,08~0,15
10	3.900	0,25~0,50	3.200	0,25~0,50	3.900	0,15~0,25	3.900	0,15~0,25	3.200	0,08~0,15

## Strategy

### 10xD / 30xD applications


#### Drill pilot hole

- $\varnothing +0,03$  mm
- Point angle  $>140^\circ$




#### Insert ADO deep hole drill until 0,2 mm above hole bottom


- $S = 500$  rev/min-1
- $V_f = 500$  mm/min
- Without coolant pressure



#### Launch coolant and machining RPM




#### Feed rate 100% until final drilling depth



When reaching final drilling depth, lower the RPM to 500 rev/min. Reverse drill out of the hole with high feed (e.g.  $V_f = 6.000$  mm/min).

**Do not reverse with max. feed!**







## Drilling pilot hole

The point angle is important. It must always be larger than that of the following tool so that the point of the deep hole drill hits the center of the of the pilot hole exactly!

The diameter should be slightly larger than that of the following tool!

- Position accuracy
- Runout

- Friction
- Wear






## Possible pilot drills for ADO-10D to 50D

- ADO-3D/5D are manufactured with outer diameter tolerance h8 and point angle  $>140^\circ$ .
- ADO deep hole drills are manufactured with outer diameter tolerance e8 and point angle  $<140^\circ$ .
- ADO-PLT, point angle  $160^\circ$ , outer diameter  $+ 0,03 \text{ mm}$

## Pilot drilling on round / inclined surfaces

- The ADF(O) series drills are suitable for pilot drilling on round / inclined surfaces.




Reference dimension (mm)		Dimensional tolerance for shafts, frequently used fits															
		Tolerance limit class															
		b9	c9	d8	d9	e7	e8	e9	f6	f7	f8	g5	g6	h5	h6	h7	h8
-	3	-140 -165	-60 -85	-20 -34	-20 -45	-14 -24	-14 -28	-14 -39	-6 -12	-6 -16	-6 -20	-2 -6	-2 -8	0 -4	0 -6	0 -10	0 -14
3	6	-140 -170	-70 -100	-30 -48	-30 -60	-20 -32	-20 -38	-20 -50	-10 -18	-10 -22	-10 -28	-4 -9	-4 -12	0 -5	0 -8	0 -12	0 -18
6	10	-150 -186	-80 -116	-40 -62	-40 -76	-25 -40	-25 -47	-25 -61	-13 -22	-13 -28	-13 -35	-5 -11	-5 -14	0 -6	0 -9	0 -15	0 -22
10	14	-150 -193	-95 -138	-50 -77	-50 -93	-32 -50	-32 -59	-32 -75	-16 -27	-16 -34	-16 -43	-6 -14	-6 -17	0 -8	0 -11	0 -18	0 -27

## Optimizing 40D / 50D drilling depths

The following measures are helpful for reliable implementation of drilling depths of up to 50xD!

Set deeper pilot hole (e.g. ADO-5D)


- Better guidance



Optional (recommended)


Use additional deep hole drill (e.g. ADO-20D, ADO-30D)

- Less runout
- Possibly faster and therefore more economical




Insert ADO-40D/50D into pre-drilled hole (keep approx. 0,2mm safety distance from hole bottom)

- Rotation **left**
- $S = 300-500$  rev/min
- Without coolant pressure




Finishing the deep hole with ADO-40D/50D

- Turn on coolant and machining rotation
- Feed rate 100% until final drilling depth



When reaching final drilling depth, lower the RPM to 300-500 rev/min. Reverse drill out of the hole with high feed (e.g.  $V_f = 6.000$  mm/min).



**Do not reverse with max. feed!**



## Optimizing tool life



Strategies for optimizing the tool life

### Pre-drilling with reduced feed rate



- Reduce feed rate to 50% until drill has reached 1xD drilling depth
- Reduce feed rate to 50% before drill exits hole

### Pre-drilling with „FLIN“ (Siemens - Sinumerik)



- Linear increase of feed rate from 50% to 100% until drill reaches 1xD depth
- Linear decrease of feed rate to 50% before drill exits the hole


## Manufacturable range as special items

Ø	Max. OAL	Max. flute length	Max. drilling depth							"Unit (mm)"								
			50	100	150	200	250	300	350	400	450							
3	209	159			150													
~4	262	212				200												
~5	315	265					250											
~6	428	378						360										
~7	456	406							380									
~8	500	450								430								
~9	500	450									420							
~10	500	450										420						
~11	500	450											420					
~12	500	450												420				
~13	500	450													410			
~14	500	450														410		
~15	500	450															410	
~16	500	450																400

Manufacturable range

# CUTTING DATA

## Low Cutting Force



— (40D)  
 Competitor  
— ADO-40D


Size:  $\varnothing 3$   
 Work Material: SCM440 (82~90HRB)  
 Cutting speed: 80m/min (8493min<sup>-1</sup>)  
 Feed: 1.188mm/min (0,14mm/rev)

## 25° Helix Angle Optimal for Ultra-Deep-Hole Drilling

Drilling | Solid carbide




Cutting Data




Helix Angle 20°

Insufficient helix angle causes clogging of chips and tool breakage



Helix Angle 25°

Stable performance



Helix Angle 30°

Low rigidity leads to unstable processing

Size:  $\varnothing 6 \times 50D$  Work Material: SCM440 (82~90HRB) Depth of Hole: 300mm

# CUTTING DATA


## Long tool life even in ultra-deep-hole drilling applications

Size	Ø8
Work Material	SCM440 (Raw material)
Depth of Cut	391mm
Coolant	Water Soluble
Machine	Horizontal machining center

Tool	Second Step		
	1	2	3
	ADO-50D	Competitor	Gun Drill
Cutting Speed	62.8m/min (2,500min <sup>-1</sup> )	70m/min (2,787min <sup>-1</sup> )	60m/min (2,389min <sup>-1</sup> )
Feed	750mm/min (0.3mm/rev)	418mm/min (0.15mm/rev)	143mm/min (0.06mm/rev)



First Step: pilot hole at depth of 40mm

		Number of Holes		Cutting Time
		100	200	
1	ADO-50D	265 Holes Still Running		1'4"
2	Competitor	60 Holes	Breakage	1'29"
3	Gun Drill	65 Holes	Wear and replacement	3'17"



## Effectively breaks chips into small and manageable pieces even in sticky work material

Tool	ADO-50D	Competitor 50D
Size	Ø5	
Work Material	SCM420H	
Cutting Speed	60m/min (3.822 min <sup>-1</sup> )	50m/min (3.185 min <sup>-1</sup> )
Feed	955m/min (0,25 mm/rev)	636m/min (0,2 mm/rev)
Depth of Hole	250mm (Blind)	
Coolant	Water-Soluble	
Machine	Multifunction Lathe	



	Number of Holes					
	100	200	300	400	500	600
ADO-50D	572 Holes Wear and replacement					
Competitor	360 Holes			Breakage		

## SWEDEN

Branch office of OSG SCANDINAVIA  
Singelgatan 7  
212 28 Malmö  
Sweden  
Tel: +46 40 41 22 55  
osg@osg-scandinavia.com

## OSG SCANDINAVIA

(For Scandinavian countries)  
Langebjergvaenget 16  
4000 Roskilde  
Denmark  
Tel: +45 46 75 65 55  
osg@osg-scandinavia.com

## OSG NETHERLANDS

Bedrijfsweg 5  
3481 MG Harmelen  
The Netherlands  
Tel: +31 348 44 2764  
info@osg-nl.com

## OSG UK

Kelsey Close, Attleborough Fields Ind Est,  
CV11 6RS, Nuneaton  
United Kingdom  
Tel: +44 (0) 1827 720 013  
uk\_sales@osg-uk.com

## OSG EUROPE LOGISTICS

Avenue Lavoisier 1  
B-1300 Z.I. Wavre - Nord  
Belgium  
Tel: +32 10 23 05 07  
info@osgeurope.com

## OSG BELUX

Avenue Lavoisier 1  
B-1300 Z.I. Wavre - Nord  
Belgium  
Tel: +32 10 23 05 11  
info@osg-belgium.com

## OSG IBÉRICA

Bekolarra 4  
E - 01010 Vitoria-Gasteiz  
Spain  
Tel: +34 945 242 400  
osg.iberica@osg-ib.com

## OSG FRANCE


Parc Icade, Paris Nord 2  
Immeuble "Le Rimbaud"  
22 Avenue des Nations  
CS66191 - 93420 Villepinte  
France  
Tel: +33 1 49 90 10 10  
sales@osg-france.com

## OSG ITALY

Via Ferrero, 65 A/B  
I - 10098 Rivoli  
Italy  
Tel: +39 0117705211  
info@osg-italia.it



# OSG IN EUROPE



## CZECH REPUBLIC, SLOVAKIA, HUNGARY

OSG Europe Logistics S.A.  
Slovakia, organizačná zložka  
Račianska 22/A, Bratislava 831 02  
Slovakia  
Tel.: +421 24 32 91 295  
info@osgeurope.com

## OSG POLAND

ul. Spółdzielcza 57  
05-074 Halinów  
Polska  
Tel: +22 760 82 71  
Mob. +48 570 677 711  
osg@osg-poland.com

## OSG ROMANIA SRL

25C, Bucuresti-Magurele Street (Sector 5)  
051431 Bucuresti  
România  
Tel: +40 21 322 07 47  
info@osgromania.ro

## OSG TURKEY

Rami Kişla Cad.No:56 Eyüp  
Istanbul 34056  
Turkey  
Tel: +90 212 565 24 00  
Fax: +90 212 565 44 00  
info@osg-turkey.com

## Vischer & Bolli AG

Machining and Workholding  
Im Schossacher 17  
CH-8600 Dübendorf  
Switzerland  
Tel.: +41 44 802 15 15  
info@vb-tools.com

## OSG GERMANY

Karl-Ehmann-Str. 25  
D - 73037 Göppingen  
Germany  
Tel: +49 7161 6064 - 0  
Fax: +49 7161 6064 - 444  
info@osg-germany.de



*shaping your dreams*

**OSG EUROPE LOGISTICS**

Avenue Lavoisier 1  
B-1300 Z.I. Wavre - Nord - Belgium  
Tel: +32 10 23 05 07  
info@osgeurope.com

**OSG POLAND Sp. z o.o.**

Spółdzielcza 57  
05-074 Halinów - Poland  
Tel: +22 760 82 71  
osg@osg-poland.com

**OSG ROMANIA SRL**

25C, Bucuresti-Magurele Street (Sector 5)  
051431 Bucuresti - România  
Tel: +40 21 322 07 47  
info@osgromania.ro

**OSG BELUX**

Avenue Lavoisier 1  
B-1300 Z.I. Wavre - Nord - Belgium  
Tel: +32 10 23 05 11  
info@osg-belgium.com

**OSG GERMANY**

Karl-Ehmann-Str. 25  
D - 73037 Göppingen - Germany  
Tel: +49 7161 6064 - 0  
Fax: +49 7161 6064 - 444  
info@osg-germany.de

**AUSTRIA**

Branch office of OSG GERMANY  
Messestraße 11  
A-6850 Dornbirn  
Tel: +49 7161 6064-0  
info@osg-germany.de

**OSG FRANCE**

Parc Icade, Paris Nord 2  
Immeuble "Le Rimbaud"  
22 Avenue des Nations  
CS66191 - 93420 Villepinte - France  
Tel: +33 1 49 90 10 10  
sales@osg-france.com

**OSG SCANDINAVIA**

(For Scandinavian countries)  
Langebjergvaenget 16  
4000 Roskilde - Denmark  
Tel: +45 46 75 65 55  
osg@osg-scandinavia.com

**OSG ITALIA**

Via Ferrero, 65 A/B3  
I - 10098 Rivoli - Italy  
Tel: +39 0117705211  
info@osg-italia.it

**OSG NETHERLANDS**

Bedrijfsweg 5 - 3481 MG Harmelen  
Tel: +31 348 44 2764  
info@osg-nl.com

**SWEDEN**

Branch office of OSG SCANDINAVIA  
Singelgatan 7  
212 28 Malmö - Sweden  
Tel: +46 40 41 22 55  
osg@osg-scandinavia.com

**Vischer & Bolli AG**

Machining and Workholding  
Im Schossacher 17  
CH-8600 Dübendorf  
T +41 44 802 15 15  
info@vb-tools.com

**OSG UK**

Kelsey Close, Attleborough Fields Ind Est,  
CV11 6RS, Nuneaton, United Kingdom.  
Tel: +44 1827 720 013  
uk\_sales@osg-uk.com

**OSG IBERICA**

Bekolarra 4  
E - 01010 Vitoria-Gasteiz - Spain  
Tel: +34 945 242 400  
osg.iberica@osg-ib.com

**CZECH, SLOVAKIA, HUNGARY**

OSG Europe Logistics S.A.  
Slovakia organizacna zlozka  
Racianská 22/A, SK-83102 Bratislava  
Slovakia  
Tel. +421 24 32 91 295  
Orders-osgsvk@osgeurope.com

**OSG TURKEY**

Rami Kışla Cad.No:56 Eyüp  
Istanbul 34056 - Turkey  
Tel+90 212 565 24 00  
Fax: +90 212 565 44 00  
info@osg-turkey.com

**OSG EUROPE LOGISTICS S.A.**

10/2024 - All rights reserved. © OSG Europe 2024

The contents of this catalogue are provided to you for viewing only. They are not intended for reproduction either in part or in whole in this or other medium. They cannot be copied, used to create derivation work or used for any reason, by means without the express, written permission of the copyright owner. If prices are stated, they are netto unit-prices and any eventual tax(es) have to be added. The company is not responsible for any printing error in technical, price and/or any other data.

Tool specifications subject to change without notice.

[www.osgeurope.com](http://www.osgeurope.com)

